Raymond St. 2200 S OFFICE OF THE MARION COUNTY SURVEYOR SECTION RECORD CORNER _____15_____ RANGE ___3__ SECTION _____24_TOWNSHIP __ DATE: 7-5-05 PARTY CHIEF: Wilcoxen CREW: . TYPE OF MARKER: Harrison ż. METHOD OF ESTABLISHMENT: ____County: 10-5-99 IN. S.P.C. E ZONE NAD '83 NAME: 15032402 498451.5340(m) N: 58624.6630(m) Ε: 2. 00 Raymond St. 2200 S 56.98' 3. 4.

Original post set 1820 by Laughlin with witness: 10" maple S 16 E 13 links, 8" dagwood N 61 W 27 links per Marion County Atlas pg. 6. Fatout 11-6-1878 called no manuments nor witness found per Center Township Legal Survey Book pg. 47. 8-30-92 Harrison set by Wilcoxen in accordance with the Raymond St. Construction project. Re-tied 10-5-99 by Kiste. Re-tied 7-5-05 by Wilcoxen.

	150324	
REF.	DISTANCE	DESCRIPTION
l.	47.71	Top nut of fire hydrant
2.	57.31'	Cut 'x' NW bolt of aluminum pole
3.	56.98	Cut 'x' in median
4.	83.24	Cut 'x' SW bolt of aluminum pole
5.	26.44	Centerline point Harrison
6.	88.82	Cut 'x' SF bolt of aluminum pole
7.	50.33'	Cut 'x' in median
8.	57.02	Cut 'x' SW bolt of aluminum pole